

## 64633 HLX

Halogen (< 75 V) Single End | OSRAM single end low voltage halogen lamps provide high quality light to meet the high demands of the medical and scientific markets



### Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead

### Product family benefits

- Compared to standard lamps up to 10 % higher luminous efficacy (HLX)
- Instant light (HLX)

### Product family features

- Xenon instead of krypton as the filler gas (XENOPHOT HLX versions)
- Luminous flux up to 10 % higher with same power consumption (XENOPHOT HLX versions)
- HLX tungsten halogen low-voltage lamp with or without reflector
- Dimmable (HLX)



# Product datasheet

## Technical data

### General Product Information

Global order reference	64633 HLX
Product number (Americas)	54250
Product name (Americas)	BRJ/EVB 64633 HLX 150W 15V 40/CS 1/SKU
Family brand	XENOPHOT (HLX)
General description	150 Watt, tungsten Halogen, low voltage without reflector
ANSI code	BRJ
LIF code	A1/234

### Electrical Data

Nominal wattage	150 W
Nominal voltage	15.0 V
Type of current	AC

### Photometric Data

Nominal luminous flux	5600 lm
Illuminated field	3.0*4.8 mm <sup>2</sup>
Color temperature	3450 K
Color rendering index Ra	100
Light center length (LCL)	30.0 mm
Light center length (LCL) - (in)	1.17 in

### Physical Attributes & Dimensions

Lamp base	G6.35
Diameter (in)	0.472 in
Diameter	11.5 mm
Length	44.0 mm
Product weight	2.40 g

### Operating Conditions

Burning position	s90
------------------	-----

### Lifetime Data

Nominal lifetime	50 hr
------------------	-------

### Environmental & Regulatory Information

## Product datasheet

### Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)

Primary article identifier	4050300006710
Date of declaration	26-06-2024
Declaration no. in SCIP database	In work
Candidate list substance 1	No declarable substances contained

### Country specific information

Product code	METEL code	SEG-No.	STK number	UK Org
4050300006710	OSRH64633HLX	-	4736533	-

## Product datasheet

---

### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300890616	64633 HLX		- x - x -	2.00 dm <sup>3</sup>	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.