

## HBO 200 W/2 49 V

HBO  $\leq$  200W Double End | Short arc lamps with an intense point source that provides a broad spectrum through the visible and ultraviolet ranges



### Areas of application

- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Microscopy
- Solar Simulation

### Product family benefits

- High radiance
- High radiant power in the UV and the visible range

### Product family features

- Multi-line spectrum



# Product datasheet

## Technical data

### General Product Information

Global order reference	HBO 200W/2 200W
------------------------	-----------------

### Electrical Data

Nominal wattage	200 W
Nominal voltage	49.0 V
Lamp voltage	47...57 V <sup>1)</sup>
Lamp current	3.0...3.5 A
Type of current	DC or AC

<sup>1)</sup> Initial electrical values

### Photometric Data

Nominal luminous flux	9500 lm
Luminous intensity	1000 cd <sup>1)</sup>
Luminous efficacy	47.5 lm/W
Light center length (LCL)	40.0 mm

<sup>1)</sup> Typical initial photometric value

### Physical Attributes & Dimensions

Base (anode)	SFc10-4
Base (cathode)	SFc10-4
Diameter (in)	39.331 in
Diameter	17.0 mm
Length	125.0 mm
Length with base excl. base pins/connection	102.00 mm <sup>1)</sup>
Product weight	32.00 g

<sup>1)</sup> Maximum

### Operating Conditions

Burning position	s90 <sup>1)</sup>
------------------	-------------------

<sup>1)</sup> Anode underneath

### Lifetime Data

Nominal lifetime	400 hr
------------------	--------

### Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)

## Product datasheet

<b>Primary article identifier</b>	4050300508283
<b>Date of declaration</b>	26-06-2024
<b>Declaration no. in SCIP database</b>	In work

## Product datasheet

---

### Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300508290	HBO 200 W/2 49 V		- x - x -	11.10 dm <sup>3</sup>	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.