# Product datasheet



# 64514 300 W 120 V

Halogen (75-130 V) Single End | Offering a broad portfolio of high quality single end halogen lamps used in the stage and studio markets




#### Areas of application

- Stage & Theatre
- Studio, TV, & Film
- Professional Photography
- Club & Disco

#### Product features and benefits

- Robust construction for reliable, lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift



March 17, 2025, 03:47:42 64514 300 W 120 V

### Technical data

### **General Product Information**

Product number (Americas)	54766	
Product name (Americas)	64514 300W 120V 20/CS 1/SKU	
ANSI code	-	
LIF code	CP/96	
Product remark	With quartz pinch technology	
Global order reference	64514	


## **Electrical Data**

Nominal wattage	300 W
Nominal voltage	120 V
Type of current	AC

### **Photometric Data**

Nominal luminous flux	8100 lm	
Color temperature	3200 К	
Color rendering index Ra	100	
Light center length (LCL) - (in)	1.053 in	

# Physical Attributes & Dimensions



Lamp base	GX6.35
Diameter (in)	0.728 in
Diameter	18.5 mm
Length	53.0 mm
Product weight	6.50 g

# **Operating Conditions**

# Product datasheet

Burning position	Other
Dimmable	Yes

### Lifetime Data

Nominal lifetime 75 hr

### Environmental & Regulatory Information

# Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Primary article identifier	4008321746139   4008321098672		
Declaration no. in SCIP database	No declarable substances contained		
Candidate list substance 1	No declarable substances contained		

### Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321098672	OSRH64514	-	-	-

# Product datasheet

#### Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321098672	64514 300 W 120 V	Folding carton box 1	42 mm x 42 mm x 111 mm	0.20 dm <sup>3</sup>	23.00 g
4008321098689	64514 300 W 120 V	Shipping carton box 12	180 mm x 127 mm x 140 mm	3.20 dm <sup>3</sup>	290.20 g
4008321746139	64514 300 W 120 V	Folding carton box 1	33 mm x 37 mm x 71 mm	0.09 dm <sup>3</sup>	14.00 g
4008321746146	64514 300 W 120 V	Shipping carton box 20	194 mm x 139 mm x 84 mm	2.27 dm <sup>3</sup>	342.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.